

M443AL , 1U 19" 3 way Power Strip



M443AL, 3 way Power Strip Specification	
Part Number	M443AL
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	3 ways
Plug	16A plug DIN49441
Inner Circuit Connection	Single
Rating Voltage	250VAC 50/60Hz.
Max.Power	4000Watt
Safety Authentication	CE
Rating Current	16A
Interior Wiring Cable	1.5mm2 (16AWG)
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	16A Miniature Circuit Breaker
MECHANICAL	
Colour	Black
Cable Specification	3x1.5mm2
Cable Length	3m.
U (44.45)mm. Size	1U
Product Size LxWxH	482.6(19")x44.4x44.4 (mm.)
Mounting Length	465mm
Case Length	430.5mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Frontal installation

M446AL, 1U 19" 6 way Power Strip



M446AL,1U19 " 6 way Power Strip Specification	
Part Number	AUE2250D3-06AHDGMB
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	6 ways
Plug	16A plug DIN49441
Inner Circuit Connection	Single
Rating Voltage	250VAC 50/60Hz.
Max.Power	4000Watt
Safety Authentication	CE
Rating Current	16A
Interior Wiring Cable	1.5mm ² (16AWG)
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	16A Miniature Circuit Breaker
MECHANICAL	
Colour	Black
Cable Specification	3x1.5mm ²
Cable Length	3m.
U (44.45)mm. Size	1U
Product Size LxWxH	482.6(19")x44.4x44.4 (mm.)
Mounting Length	465mm
Case Length	430.5mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Frontal installation

M446STD, 1U 19" 6 way Power Strip



M446STD,1U19 " 6 way Power Strip Specification	
Part Number	AUE2250D3-06AHDCMB
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	6 ways
Plug	16A plug DIN49442
Inner Circuit Connection	Single
Rating Voltage	250VAC 50/60Hz.
Max.Power	4000Watt
Safety Authentication	CE
Rating Current	16A
Interior Wiring Cable	1.5mm ² (16AWG)
Protection	ON/OFF
FUNCTIONS	
Control Function	16A lighted ON/OFF switch
MECHANICAL	
Colour	Black
Cable Specification	3x1.5mm ²
Cable Length	3m.
U (44.45)mm. Size	1U
Product Size LxWxH	482.6(19")x44.4x44.4 (mm.)
Mounting Length	465mm
Case Length	430.5mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Frontal installation

M449AL, 2U 19" 9 way Power Strip



M449AL,2U19 " 9 way Power Strip Specification	
Part Number	AUE2260D3-09AHDGMB
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	9 ways
Plug	16A plug DIN49441
Inner Circuit Connection	Single
Rating Voltage	250VAC 50/60Hz.
Max.Power	4000Watt
Safety Authentication	CE
Rating Current	16A
Interior Wiring Cable	Combined Copper
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	16A Miniature Circuit Breaker
MECHANICAL	
Colour	Black
Cable Specification	3x1.5mm ²
Cable Length	3m.
U (44.45)mm. Size	2U
Product Size LxWxH	482.6(19")x44.4x88.8 (mm.)
Mounting Length	465mm
Case Length	430.5mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Frontal installation

M446AL SP, 1U 19" 6 way Power Strip



M446AL SP, 1U 19" 6 way Power Strip Specification	
Part Number	AUE2250D3-06AHDCHB
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	6 ways
Plug	16A plug DIN49441
Inner Circuit Connection	Single
Rating Voltage	250VAC 50/60Hz.
Max.Power	4000Watt
Safety Authentication	CE
Rating Current	16A
Interior Wiring Cable	1.5mm ² (16AWG)
Protection	Surge Protection
FUNCTIONS	
Control Function	16A lighted ON/OFF switch
MECHANICAL	
Colour	Black
Cable Specification	3x1.5mm ²
Cable Length	3m.
U (44.45)mm. Size	1U
Product Size LxWxH	482.6(19")x44.4x44.4 (mm.)
Mounting Length	465mm
Case Length	430.5mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Frontal installation

M446AL UK, 1.4U 19" 6 way Power Strip



M446ALUK,1.4U19 " 6 way Power Strip Specification	
Part Number	AUE2220B1-06AHBCMB
ELECTRICAL Features	Detailed Description
Socket Type	BS1363 UK type Socket
Socket Quantity	6 ways
Plug	13A plug BS1363
Inner Circuit Connection	Single
Rating Voltage	250VAC 50/60Hz.
Max.Power	4000Watt
Safety Authentication	CE
Rating Current	13A
Interior Wiring Cable	1.5mm ² (16AWG)
Protection	ON/OFF
FUNCTIONS	
Control Function	16A lighted ON/OFF switch
MECHANICAL	
Colour	Black
Cable Specification	3x1.5mm ²
Cable Length	3m.
U (44.45)mm. Size	1.4U
Product Size LxWxH	482.6(19")x44.4x62 (mm.)
Mounting Length	465mm
Case Length	430.5mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Frontal installation

M44 6AL IEC AMP, 1U 19" 6 way Power Strip



M446ALIEC AMP, 1U 19" 6 way Power Strip Specification	
Part Number	AUE2250C2-06AHEGDB
ELECTRICAL Features	Detailed Description
Socket Type	IEC320 C13
Socket Quantity	6 ways
Plug	IEC60309 plug (16A 2P+E)
Inner Circuit Connection	Single
Rating Voltage	250VAC 50/60Hz.
Max.Power	4000Watt
Safety Authentication	CE
Rating Current	13A
Interior Wiring Cable	1.5mm2 (16AWG)
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	16A Miniature Circuit Breaker
Monitor Function	32A Amp. Meter
MECHANICAL	
Colour	Black
Cable Specification	3x1.5mm2
Cable Length	3m.
U (44.45)mm. Size	1U
Product Size LxWxH	482.6(19")x44.4x44.44 (mm.)
Mounting Length	465mm
Case Length	430.5mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Frontal installation

M44 24AL IEC, 1.4U 20+4 way Power Strip



M44 24AL IEC, 1.4U 20+4 WAY POWER STRIP SPECIFICATION	
Part Number	AUE2220H1-24AVFN
ELECTRICAL Features	Detailed Description
Socket Type	IEC320 C13, IEC320 C19
Socket Quantity	20 ways:C13 + 4 ways:C19
Plug	IEC60309 plug (32A 2P+E)
Inner Circuit Connection	Double
Rating Voltage	250VAC 50/60Hz.
Max.Power	8000Watt
Safety Authentication	CE
Rating Current	32A
Interior Wiring Cable	2.5mm ²
Protection	Direct connection to system
FUNCTIONS	
Control Function	Direct
Monitor Function	32A Amp. Meter
MECHANICAL	
Colour	Black
Cable Specification	3x6mm ²
Cable Length	3m.
U (44.45)mm. Size	1.4U
Product Size LxWxH	1346x44.4x62mm
Mounting Length	1336mm
Case Length	1338mm
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Inverse installation

M44 24AL IEC MCB, 1.4U 20+4 way Power Strip



M44 24AL IEC MCB, 1.4U 20+4 way Power Strip Specification	
Part Number	AUE2220H1-24AVFTDB
ELECTRICAL Features	Detailed Description
Socket Type	IEC320 C13, IEC320 C19
Socket Quantity	20 ways:C13 + 4 ways:C19
Plug	IEC60309 plug (32A 2P+E)
Inner Circuit Connection	Double
Rating Voltage	250VAC 50/60Hz.
Max.Power	8000Watt
Safety Authentication	CE
Rating Current	32A
Interior Wiring Cable	1.5mm ² per circuit
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	2ea. 16A Miniature Circuit Breaker
Monitor Function	2ea. 32A Amp. Meter
MECHANICAL	
Colour	Black
Cable Specification	3x6mm ²
Cable Length	3m.
U (44.45)mm. Size	1.4U
Product Size LxWxH	1648x44.4x62mm
Mounting Length	1620mm
Case Length	1592mm
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Inverse installation

M44 20AL IEC MONITOR, 2U 20 way Power Strip



M44 20AL IEC MONITOR, 2U 20 way Power Strip Specification	
Part Number	NA412H2022
ELECTRICAL Features	Detailed Description
Socket Type	IEC320 C13, IEC320 C19
Socket Quantity	16 ways:C13 + 4 ways:C19
Plug	IEC60309 plug (32A 2P+E)
Inner Circuit Connection	Double
Rating Voltage	250VAC 50/60Hz.
Max.Power	8000Watt
Safety Authentication	CE
Rating Current	32A
Interior Wiring Cable	2.5mm ²
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	2ea. 16A Miniature Circuit Breaker
Monitor Function	Total current Operating Status of PDU Temperature/Humidity state Smoke state Waterlogging state Door open state
Settings	Limiting range of total load current Limiting range of temperature and humidity
Alarm Function	Total load current exceeds the limiting value System goes wrong Smoke Waterlogging Door opening
Alarm Type	On PDU:Flashing indicator and buzzer Web interface: flashing indicator and buzzer in PC alarms Automatic E-mail sending to system administrator SNMP sends alarm information Automatic alarm with wireless telecommunications
Current Consumption Measurement	Automatic record the current consumption in unit time
Log record	Record and save the operating information of NMP, provide the query and outlet of records
User Management	Set users's right
Turn off	Remotely soft turn off
Accessing Method	Web, access through IE SNMP (V1/V2C/V3) access to control through standard network working station Telnet, SSH, Access to control through command controlling station

M44 20AL IEC MONITOR, 2U 20 way Power Strip



MECHANICAL	
Colour	Black
Cable Specification	3x6mm3
Cable Length	3m.
U (44.45)mm. Size	2U
Product Size LxWxH	1744x88.8x44.4mm
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Inverse installation

M44 20AL IEC SMART, 2U 20 way Power Strip



M44 20AL IEC SMART, 2U 20 way Power Strip Specification	
Part Number	ND412H2022
ELECTRICAL Features	Detailed Description
Socket Type	IEC320 C13, IEC320 C19
Socket Quantity	16 ways:C13 + 4 ways:C19
Plug	IEC60309 plug (32A 2P+E)
Inner Circuit Connection	Double
Rating Voltage	250VAC 50/60Hz.
Max.Power	8000Watt
Safety Authentication	CE
Rating Current	32A
Interior Wiring Cable	2.5mm2
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	2ea. 16A Miniature Circuit Breaker
Monitor Function	Total current Load current of each outlet On/off state of each outlet Operating Status of PDU Temperature/Humidity state Smoke state Waterlogging state Door open state Server Operating Status
Settings	Limiting range of total load current Limiting range of temperature and humidity Limiting range of the load current of each outlet
Alarm Function	Total load current exceeds the limiting value Load current of individual outlet exceed the limiting value Individual outlet goes wrong System goes wrong Smoke Waterlogging Door opening
Alarm Type	On PDU:Flashing indicator and buzzer Web interface: flashing indicator and buzzer in PC alarms Automatic E-mail sending to system administrator SNMP sends alarm information Automatic alarm with wireless telecommunications
Current Consumption Measurement	Automatic record the current consumption in unit time
Log record	Record and save the operating information of NMP, provide the query and outlet of records
User Management	Set users's right
Turn off	Remotely soft turn off
Accessing Method	Web, access through IE SNMP (V1/V2C/V3) access to control through standard network working station Telnet, SSH, Access to control through command controlling station

M44 20AL IEC SMART, 2U 20 way Power Strip



MECHANICAL	
Colour	Black
Cable Specification	3x6mm3
Cable Length	3m.
U (44.45)mm. Size	2U
Product Size LxWxH	1744x88.8x44.4mm
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Inverse installation

EM GRP319A, 1U 19" 3 way Power Strip



EMGRP319A,1U19 " 3 way Power Strip Specification	
Part Number	EM GRP319A
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	3 way
Plug	16A plug DIN49442
Inner Circuit Connection	Single
Rating Voltage	250VAC 50/60Hz.
Max.Power	4000Watt
Safety Authentication	CE
Rating Current	16A
Interior Wiring Cable	1.5mm2 (16AWG)
Protection	ON/OFF
FUNCTIONS	
Control Function	16A lighted ON/OFF switch
MECHANICAL	
Colour	Black
Cable Specification	3x1.5mm2
Cable Length	3m.
U (44.45)mm. Size	1U
Product Size LxWxH	482.6(19")x44.4x44.44 (mm.)
Material	PVC Profile
Power Input	Left end side
Bracket Install	Frontal installation

EM GRP619A, 1U 19" 6 way Power Strip



EMGRP619A, 1U 19" 6 way Power Strip Specification	
Part Number	EM GRP619A
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	6 way
Plug	16A plug DIN49442
Inner Circuit Connection	Single
Rating Voltage	250VAC 50/60Hz.
Max.Power	4000Watt
Safety Authentication	CE
Rating Current	16A
Interior Wiring Cable	1.5mm ² (16AWG)
Protection	ON/OFF
FUNCTIONS	
Control Function	16A lighted ON/OFF switch
MECHANICAL	
Colour	Black
Cable Specification	3x1.5mm ²
Cable Length	3m.
U (44.45)mm. Size	1U
Product Size LxWxH	482.6(19")x44.4x44.44 (mm.)
Material	PVC Profile
Power Input	Left end side
Bracket Install	Frontal installation

M441847ALD, 1.4U 18 way Power Strip



M441847ALD,1.4U 18way Power Strip Specification	
Part Number	M441847ALD
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	18 way
Plug	No plug
Inner Circuit Connection	Double (9+9)
Rating Voltage	250VAC 50/60Hz.
Max.Power	8000Watt
Safety Authentication	CE
Rating Current	32A
Interior Wiring Cable	4mm2
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	2ea. 16A Miniature Circuit Breaker
MECHANICAL	
Colour	Aluminium Grey
Cable Specification	No cable
U (44.45)mm. Size	1.4U
Product Size LxWxH	Length=2000mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Bottom
Bracket Install	Inverse or Frontal installation

M441842ALD, 1.4U 18 way Power Strip



M441842ALD,1.4U 18way Power Strip Specification	
Part Number	M441842ALD
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	18 way
Plug	No plug
Inner Circuit Connection	Double (9+9)
Rating Voltage	250VAC 50/60Hz.
Max.Power	8000Watt
Safety Authentication	CE
Rating Current	32A
Interior Wiring Cable	4mm ²
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	2ea. 16A Miniature Circuit Breaker
MECHANICAL	
Colour	Aluminium Grey
Cable Specification	No cable
U (44.45)mm. Size	1.4U
Product Size LxWxH	Length=1800mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Bottom
Bracket Install	Inverse or Frontal installation

M441842ALD, 1.4U 18 way Power Strip



M442442ALD,1.4U 24way Power Strip Specification	
Part Number	M442442ALD
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	24 way
Plug	No plug
Inner Circuit Connection	Double (12+12)
Rating Voltage	250VAC 50/60Hz.
Max.Power	8000Watt
Safety Authentication	CE
Rating Current	32A
Interior Wiring Cable	4mm2
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	2ea. 16A Miniature Circuit Breaker
MECHANICAL	
Colour	Aluminium Grey
Cable Specification	No cable
U (44.45)mm. Size	1.4U
Product Size LxWxH	Length=1800mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Bottom
Bracket Install	Inverse or Frontal installation

M441836ALD, 1.4U 18 way Power Strip



M441836ALD,1.4U 18way Power Strip Specification	
Part Number	M441836ALD
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	18 way
Plug	No plug
Inner Circuit Connection	Double (9+9)
Rating Voltage	250VAC 50/60HZ.
Max.Power	8000Watt
Safety Authentication	CE
Rating Current	32A
Interior Wiring Cable	4mm2
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	2ea. 16A Miniature Circuit Breaker
MECHANICAL	
Colour	Aluminium Grey
Cable Specification	No cable
U (44.45)mm. Size	1.4U
Product Size LxWxH	Length=1550mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Bottom
Bracket Install	Inverse or Frontal installation

M441226ALD, 1.4U 12 way Power Strip



M441226ALD,1.4U12way Power Strip Specification	
Part Number	M441226ALD
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	12 way
Plug	No plug
Inner Circuit Connection	Double (6+6)
Rating Voltage	250VAC 50/60Hz.
Max.Power	8000Watt
Safety Authentication	CE
Rating Current	32A
Interior Wiring Cable	4mm2
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	2ea. 16A Miniature Circuit Breaker
MECHANICAL	
Colour	Aluminium Grey
Cable Specification	No cable
U (44.45)mm. Size	1.4U
Product Size LxWxH	Length=1100mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Bottom
Bracket Install	Inverse or Frontal installation

M446ALD, 1U 6 way Power Strip



M446ALD,1U6way Power Strip Specification	
Part Number	M446ALD
ELECTRICAL Features	Detailed Description
Socket Type	DIN49440 Socket Schuko
Socket Quantity	6 way
Plug	16A plug DIN49441
Inner Circuit Connection	Double (3+3)
Rating Voltage	250VAC 50/60Hz.
Max.Power	4000Watt
Safety Authentication	CE
Rating Current	16A
Interior Wiring Cable	1.5mm ² (16AWG)
Protection	Air Circuit Breaker
FUNCTIONS	
Control Function	16A Miniature Circuit Breaker
MECHANICAL	
Colour	Black
Cable Specification	3x1.5mm ²
Cable Length	3m.
U (44.45)mm. Size	1U
Product Size LxWxH	482.6(19")x44.4x44.4 (mm.)
Mounting Length	465mm
Case Length	430.5mm.
Logo	RoHS
Material	Aluminium Profile
Power Input	Left end side
Bracket Install	Frontal installation