

Shielded solution, punch-down



QuickLine® RJ45 panel, shielded

1 RU, 24 ports

Product description:

- 19" panel shielded with 24 RJ45 jacks
- IDC connector can accept 22-26 AWG solid and stranded cables
- TIA/EIA 568 A&B wiring, easy installation
- Termination: using of punch down tool 110 or Krone tool
- Meets the requirements of class E according to ISO/IEC 11801:2002 2nd ed.
- Minimum link length: 20 m
- Minimum length of patch cords: 2 m
- Third party certified
- Colour: black, RAL 9005

Article no.: 9ZQ00011

Pcs. per packing unit: 1

QuickLine® 2 port wall outlet 80 x 80, shielded

German style

Product description:

- Plastic cover frame 80 x 80 mm with rectangular central plate 50 x 50 mm
- TIA/EIA 568 A&B wiring, easy installation
- Dual type IDC connector can accept 22-26 AWG solid and stranded cables
- Termination: using of punch down tool 110 or Krone tool
- Shielded version protects against EMI/RFI interference
- Meets the requirements of class E according to ISO/IEC 11801:2002 2nd ed.
- RoHS compliant
- Minimum link length: 20 m
- Minimum length of patch cords: 2 m
- Third party certified
- Colour: white, RAL 9010

Article no.: 9ZE70009 (cable entry: left/right)
9ZE70010 (cable entry: top/bottom)

Pcs. per packing unit: 12

Transmission channel

